

Safety Guidelines

1. Nylon strap **must** be attached to a belt; **not** just through your pants' belt loop.
2. Use one safety tether per tool.
3. Discard product if cables or hardware are damaged or weakened.
4. Breaking strength: about 50kg (110 lb).

Attaching the Nylon Belt Loop

Secure the nylon belt loop to your belt by sliding the belt through the large loop or using a cow hitch*. Clip the large safety hook to the small loop on the nylon strap.

**How to tie a cow hitch:*

- a. Place the nylon strap under the belt, such that the smaller loop is at the bottom.
- b. Fold the large loop over the belt and feed the small loop through the large loop.
- c. Pull the small loop to tighten the hitch.



Cow Hitch



Tool with Integral Hang-Hole



Tool with Closed Handle

Attaching Tool Loop onto Tool

Tool with Integral Hang-Hole: Insert the bight end of the tool loop through the hang-hole such that the brass lug restrains the tool.

Tool with Closed Handle: Insert the bight end of the tool loop through the closed handle and secure the tool loop using a cow hitch, such that the brass lug rests near the closed handle.

Once the tool loop is attached to your tool, slide the bight end of the tool loop onto the split ring, and clip the small safety hook to the split ring



www.leevalley.com

1090 Morrison Drive 814 Proctor Avenue
Ottawa ON K2H 1C2 Ogdensburg NY 13669-2205
Canada United States
1-800-267-8761 1-800-267-8735